

*Amendments to the Claims*

This listing of claims replaces all prior versions, and listings, of claims in the application.

1-35. (canceled)

36. (currently amended) An arrangement for variably supporting a display, the ~~system~~ arrangement comprising,
- (a) an overhead track,
  - (b) a carriage coupled to said overhead track such that ~~the said~~ carriage can be variably positioned along said overhead track,
  - (c) a first arm coupled to and suspended from said carriage such that said first arm can be variably swiveled about the coupling to said carriage,
  - (d) a second arm coupled to said first arm such that said second arm can be variably ~~pivoted~~ positioned in different inclinations to said first arm and such that said second arm can be variably swiveled relative to said first arm about a first swivel axis ~~the coupling to said first arm~~, and
  - (e) a display coupled to said second arm by a subassembly, said subassembly comprising,
    - (i) a swivel member,
    - (ii) a mounting member affixed to a housing of said display, and
    - (iii) an elongate member extending between and connecting together said swivel member and said mounting member,
    - (iv) wherein,
      - (A) said swivel member is coupled to said second arm such that said mounting member can be variably swiveled relative to said second arm about a second swivel axis, said second swivel axis generally extending in parallel relation to said first swivel axis, and
      - (B) said elongate member is mounted to said swivel member for movement about a first pivot axis and is mounted to said mounting member for movement about a second pivot axis, said second swivel axis extending through said elongate member ~~and suspended~~

~~from said carriage such that said display can be variably pivoted  
and swiveled about the coupling to said second arm,~~

- (f) wherein said second arm comprises a pair of parallel elongate members joined to form a four-bar-linkage parallelogram such that said first swivel axis and said second swivel axis remain in parallel relation during movement of said second arm between positions having varying inclinations to said first arm~~each coupled to said first arm and coupled to said display.~~

37-38. (canceled)

39. (currently amended) An arrangement for variably supporting a display, the ~~system~~ arrangement comprising,

- (a) a first arm mounted to a support by a coupling such that said first arm can be variably swiveled about the coupling to said support,
- (b) a second arm coupled to said first arm such that said second arm can be variably positioned in different inclinations to said first arm and such that said second arm can be variably swiveled relative to said first arm about a first swivel axis~~pivoted and swiveled about the coupling to said first arm,~~ and
- (c) a display coupled to said second arm by a subassembly, said subassembly comprising,
- (i) a swivel member,
- (ii) a mounting member affixed to a housing of said display, and
- (iii) an elongate member extending between and connecting together said swivel member and said mounting member,
- (iv) wherein,
- (A) said swivel member is coupled to said second arm such that said mounting member can be variably swiveled relative to said second arm about a second swivel axis, said second swivel axis generally extending in parallel relation to said first swivel axis, and
- (B) said elongate member is mounted to said swivel member for movement about a first pivot axis and is mounted to said mounting member for movement about a second pivot axis, said second

swivel axis extending through said elongate member—and  
~~suspended from said support such that said display can be variably~~  
~~pivoted and swiveled about the coupling to said second arm,~~

- (d) wherein said second arm comprises a pair of parallel elongate members joined to  
form a four-bar-linkage parallelogram such that said first swivel axis and said  
second swivel axis remain in parallel relation during movement of said second  
arm between positions having varying inclinations to said first arm~~each coupled~~  
~~to said first arm and coupled to said display.~~

40. (canceled)
41. (previously presented)The arrangement of claim 39, wherein said first arm is mounted to a wall.
42. (previously presented)The arrangement of claim 39, wherein said first arm is mounted to a ceiling.
43. (new) The arrangement of claim 39, wherein said second swivel axis extends through said display.
44. (new) The arrangement of claim 39, wherein said first pivot axis is coplanar with said second swivel axis.
45. (new) The arrangement of claim 44, wherein said first pivot axis intersects said second swivel axis.
46. (new) The arrangement of claim 36, wherein said second swivel axis extends through said display.
47. (new) The arrangement of claim 36, wherein said first pivot axis is coplanar with said second swivel axis.
48. (new) The arrangement of claim 47, wherein said first pivot axis intersects said second swivel axis.